

10/19/00



Please check a plus sign (+) inside this box → +

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No	24-AT-5990
First Named Inventor or Application Identifier	Roy C Challberg
Title	CORE SUPPORT FOR AN F-LATTICE CORE OF A BOILING WATER NUCLEAR REACTOR
Express Mail Label No.	EL319732601US

JC 825 U.S. PTO  
09/692135

10/19/00

**APPLICATION ELEMENTS**

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:  
Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

- |   |  |
|---|--|
| 1. <input checked="" type="checkbox"/> Fee Transmittal Form (e.g., PTO/SB/17)<br>(Submit an original, and a duplicate for fee processing) | 6. <input type="checkbox"/> Microfiche Computer Program (Appendix)   |
| 2. <input checked="" type="checkbox"/> Specification [Total Pages]<br>(Preferred arrangement set forth below)                             | 7. <input type="checkbox"/> Nucleotide and/or Amino Acid Sequence Submission<br>(If applicable, all necessary) |
| 14  |  |
| - Descriptive title of the Invention  | a. <input type="checkbox"/> Computer Readable Copy   |
| - Cross References to Related Applications  | b. <input type="checkbox"/> Paper Copy (identical to computer copy)  |
| - Statement Regarding Fed sponsored R & D   | c. <input type="checkbox"/> Statement verifying identity of above copies                                       |
| - Reference to Microfiche Appendix  |  |
| - Background of the Invention   |  |
| - Brief Summary of the Invention  |  |
| - Brief Description of the Drawings (if filed)  |  |
| - Detailed Description  |  |
| - Claim(s)  |  |
| - Abstract of the Disclosure  |  |
- 
- |  |    |
|--|----|
| 3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) [Total Sheets]  | 11 |
| 4. Oath or Declaration [Total Pages]   | 2  |
| a. <input checked="" type="checkbox"/> Newly executed (original or copy)<br>b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d))<br><i>(for continuation/divisional with Box 17 completed)</i><br><i>[Note Box 5 below]</i>  |    |
| <input type="checkbox"/> DELETION OF INVENTOR(S)<br><i>Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).</i>   |    |
| 5. <input type="checkbox"/> Incorporation by Reference (useable if Box 4b is checked)<br><i>The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein</i> |    |

**ACCOMPANYING APPLICATION PARTS**

- |  |  |
|--|--|
| 8. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s))   | 9. <input type="checkbox"/> 37 CFR 3.73(b) Statement <input checked="" type="checkbox"/> Power of Attorney<br><i>(when there is an assignee)</i> |
| 10. <input type="checkbox"/> English Translation Document (if applicable)  | 11. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations                    |
| 12. <input type="checkbox"/> Preliminary Amendment   | 13. <input type="checkbox"/> Return Receipt Postcard (MPEP 503)<br><i>(Should be specifically itemized)</i>                                      |
| 14. <input type="checkbox"/> Small Entity <input type="checkbox"/> Statement filed in prior application, Statement(s) Status still proper and desired<br><i>(PTO/SB/09-12)</i> | 15. <input type="checkbox"/> Certified Copy of Priority Document(s)<br><i>(If foreign priority is claimed)</i>                                   |
| 16. <input checked="" type="checkbox"/> Other: Certificate of Express Mailing  |  |

\*NOTE FOR ITEMS 1 & 14 IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 CFR § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 CFR § 1.28)

## 17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

Continuation  Divisional  Continuation-in-part (CIP) of prior application No \_\_\_\_\_  
 Prior application information Examiner \_\_\_\_\_ Group/Art Unit \_\_\_\_\_

**18. CORRESPONDENCE ADDRESS**

Customer Number or Bar Code Label \_\_\_\_\_ or  Correspondence address below  
 (Insert Customer No. or Attach bar code label here)

NAME	John S. Beulick Armstrong Teasdale LLP				
ADDRESS	Suite 2600 One Metropolitan Square				
CITY	St. Louis	STATE	MO	ZIP CODE	63102-2740
COUNTRY	U.S.A.	TELEPHONE	(314) 621-5070		FAX (314) 621-5065

Name (Print/type)	Michael Tersillo	Registration No. (Attorney/Agent)	42,180
Signature	<i>Michael Tersillo</i>	Date	10/19/00

Burden Hour Statement This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Office, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Under the paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

<b>FEE TRANSMITTAL</b>		<i>Complete If Known</i>	
<p><i>Patent fees are subject to annual revision on October 1.</i>  <i>These are the fees effective October 1, 1997.</i>  <i>Small entity payments must be supported by a small entity statement, otherwise large entity fees must be paid. See Forms PTO/SB/09-12.</i>  <i>See 37 C.F.R. §§ 1.27 and 1.28.</i></p>		<b>Application Number</b>	
		<b>Filing Date</b>	
		<b>First Named Inventor</b>	Roy C. Challberg
		<b>Group Art Unit</b>	
		<b>Examiner Name</b>	
<b>TOTAL AMOUNT OF PAYMENT</b>	\$710.00	<b>Attorney Docket Number</b>	24-AT-5990

<b>METHOD OF PAYMENT (check one)</b>				<b>FEES CALCULATION (continued)</b>																																																																																																																											
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge indicated fees and credit any over payments to:  Deposit Account Number 01-2384  Deposit Account Name _____  <input checked="" type="checkbox"/> Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17 <input type="checkbox"/> Charge the Issue Fee Set in 37 CFR 1.16 at the Mailing of the Notice of Allowance				<table border="1"> <thead> <tr> <th>Large Entity Fee Code (\$)</th> <th>Small Entity Fee Code (\$)</th> <th>Fee Description</th> <th>Fee Paid</th> </tr> </thead> <tbody> <tr><td>105</td><td>130</td><td>205</td><td>65 Surcharge - late filing fee or oath</td></tr> <tr><td>127</td><td>50</td><td>227</td><td>25 Surcharge-late provisional filing fee or cover sheet</td></tr> <tr><td>139</td><td>130</td><td>139</td><td>130 Non-English specification</td></tr> <tr><td>147</td><td>2520</td><td>147</td><td>2520 For filing a request for reexamination</td></tr> <tr><td>112</td><td>920*</td><td>112</td><td>920* Requesting publication of SIR prior to Examiner action</td></tr> <tr><td>113</td><td>1840*</td><td>113</td><td>1840*Requesting publication of SIR after Examiner action</td></tr> <tr><td>115</td><td>110</td><td>216</td><td>55 Extension for reply within first month</td></tr> <tr><td>116</td><td>380</td><td>216</td><td>190 Extension for reply within second Month</td></tr> <tr><td>117</td><td>870</td><td>217</td><td>435 Extension for reply within third month</td></tr> <tr><td>118</td><td>1360</td><td>218</td><td>680 Extension for reply within fourth Month</td></tr> <tr><td>128</td><td>1850</td><td>228</td><td>925 Extension for reply within fifth month</td></tr> <tr><td>119</td><td>300</td><td>219</td><td>150 Notice of Appeal</td></tr> <tr><td>120</td><td>300</td><td>220</td><td>150 Filing a brief in support of an appeal</td></tr> <tr><td>121</td><td>260</td><td>221</td><td>130 Request for oral hearing</td></tr> <tr><td>138</td><td>1510</td><td>138</td><td>1510 Petition to institute a public use Proceeding</td></tr> <tr><td>140</td><td>110</td><td>240</td><td>55 Petition to revive - unavoidable</td></tr> <tr><td>141</td><td>1210</td><td>241</td><td>605 Petition to revive - unintentional</td></tr> <tr><td>142</td><td>1210</td><td>242</td><td>605 Utility issue fee (or reissue)</td></tr> <tr><td>143</td><td>430</td><td>243</td><td>215 Design issue fee</td></tr> <tr><td>144</td><td>580</td><td>244</td><td>290 Plant issue fee</td></tr> <tr><td>122</td><td>130</td><td>122</td><td>130 Petitions to the Commissioner</td></tr> <tr><td>123</td><td>50</td><td>123</td><td>50 Petitions related to provisional Applications</td></tr> <tr><td>126</td><td>240</td><td>126</td><td>240 Submission of Information</td></tr> <tr><td>581</td><td>40</td><td>581</td><td>40 Recording each patent assignment per property (times number of properties)</td></tr> <tr><td>146</td><td>690</td><td>246</td><td>395 Filing a submission after final rejection (37 CFR 1.129(a))</td></tr> <tr><td>149</td><td>690</td><td>249</td><td>395 For each additional invention to be examined (37 CFR 1.129(b))</td></tr> <tr><td colspan="4">Otherfee (specify) _____</td></tr> <tr><td colspan="4">Otherfee (specify) _____</td></tr> <tr> <td colspan="4">*Reduced by Basic Filing Fee Paid      SUBTOTAL (3) _____</td> </tr> </tbody> </table>				Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid	105	130	205	65 Surcharge - late filing fee or oath	127	50	227	25 Surcharge-late provisional filing fee or cover sheet	139	130	139	130 Non-English specification	147	2520	147	2520 For filing a request for reexamination	112	920*	112	920* Requesting publication of SIR prior to Examiner action	113	1840*	113	1840*Requesting publication of SIR after Examiner action	115	110	216	55 Extension for reply within first month	116	380	216	190 Extension for reply within second Month	117	870	217	435 Extension for reply within third month	118	1360	218	680 Extension for reply within fourth Month	128	1850	228	925 Extension for reply within fifth month	119	300	219	150 Notice of Appeal	120	300	220	150 Filing a brief in support of an appeal	121	260	221	130 Request for oral hearing	138	1510	138	1510 Petition to institute a public use Proceeding	140	110	240	55 Petition to revive - unavoidable	141	1210	241	605 Petition to revive - unintentional	142	1210	242	605 Utility issue fee (or reissue)	143	430	243	215 Design issue fee	144	580	244	290 Plant issue fee	122	130	122	130 Petitions to the Commissioner	123	50	123	50 Petitions related to provisional Applications	126	240	126	240 Submission of Information	581	40	581	40 Recording each patent assignment per property (times number of properties)	146	690	246	395 Filing a submission after final rejection (37 CFR 1.129(a))	149	690	249	395 For each additional invention to be examined (37 CFR 1.129(b))	Otherfee (specify) _____				Otherfee (specify) _____				*Reduced by Basic Filing Fee Paid      SUBTOTAL (3) _____			
Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid																																																																																																																												
105	130	205	65 Surcharge - late filing fee or oath																																																																																																																												
127	50	227	25 Surcharge-late provisional filing fee or cover sheet																																																																																																																												
139	130	139	130 Non-English specification																																																																																																																												
147	2520	147	2520 For filing a request for reexamination																																																																																																																												
112	920*	112	920* Requesting publication of SIR prior to Examiner action																																																																																																																												
113	1840*	113	1840*Requesting publication of SIR after Examiner action																																																																																																																												
115	110	216	55 Extension for reply within first month																																																																																																																												
116	380	216	190 Extension for reply within second Month																																																																																																																												
117	870	217	435 Extension for reply within third month																																																																																																																												
118	1360	218	680 Extension for reply within fourth Month																																																																																																																												
128	1850	228	925 Extension for reply within fifth month																																																																																																																												
119	300	219	150 Notice of Appeal																																																																																																																												
120	300	220	150 Filing a brief in support of an appeal																																																																																																																												
121	260	221	130 Request for oral hearing																																																																																																																												
138	1510	138	1510 Petition to institute a public use Proceeding																																																																																																																												
140	110	240	55 Petition to revive - unavoidable																																																																																																																												
141	1210	241	605 Petition to revive - unintentional																																																																																																																												
142	1210	242	605 Utility issue fee (or reissue)																																																																																																																												
143	430	243	215 Design issue fee																																																																																																																												
144	580	244	290 Plant issue fee																																																																																																																												
122	130	122	130 Petitions to the Commissioner																																																																																																																												
123	50	123	50 Petitions related to provisional Applications																																																																																																																												
126	240	126	240 Submission of Information																																																																																																																												
581	40	581	40 Recording each patent assignment per property (times number of properties)																																																																																																																												
146	690	246	395 Filing a submission after final rejection (37 CFR 1.129(a))																																																																																																																												
149	690	249	395 For each additional invention to be examined (37 CFR 1.129(b))																																																																																																																												
Otherfee (specify) _____																																																																																																																															
Otherfee (specify) _____																																																																																																																															
*Reduced by Basic Filing Fee Paid      SUBTOTAL (3) _____																																																																																																																															
<b>FEES CALCULATION</b>																																																																																																																															
<p><b>1. FILING FEE</b></p> <table border="1"> <thead> <tr> <th>Large Entity Fee Code (\$)</th> <th>Small Entity Fee Code (\$)</th> <th>Fee Description</th> <th>Fee Paid</th> </tr> </thead> <tbody> <tr><td>101</td><td>710</td><td>201</td><td>355 Utility Filing Fee 710.00</td></tr> <tr><td>106</td><td>320</td><td>206</td><td>160 Design Filing Fee</td></tr> <tr><td>107</td><td>490</td><td>207</td><td>245 Plant Filing Fee</td></tr> <tr><td>108</td><td>710</td><td>208</td><td>355 Reissue filing Fee</td></tr> <tr><td>114</td><td>150</td><td>214</td><td>75 Provisional Filing Fee</td></tr> <tr> <td colspan="4">SUBTOTAL (1) \$ 710.00</td> </tr> </tbody> </table> <p><b>2. CLAIMS</b></p> <table border="1"> <thead> <tr> <th>Total Claims</th> <th>Extra *20</th> <th>Fee From Below</th> <th>Fee Paid</th> </tr> </thead> <tbody> <tr> <td>16</td> <td>0</td> <td>x 0.00</td> <td>= 0.00</td> </tr> <tr> <td>2</td> <td>* 3</td> <td>0</td> <td>= 0.00</td> </tr> <tr> <td colspan="4">Multiple Dependant Claims</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Large Entity Fee Code (\$)</th> <th>Small Entity Fee Code (\$)</th> <th>Fee Description</th> </tr> </thead> <tbody> <tr><td>102</td><td>18</td><td>201 9 Claims in excess of 20</td></tr> <tr><td>102</td><td>80</td><td>202 39 Independent claims in excess of 3</td></tr> <tr><td>104</td><td>206</td><td>204 130 Multiple dependent claim</td></tr> <tr><td>109</td><td>78</td><td>209 39 Reissue independent claims over original patent</td></tr> <tr><td>110</td><td>18</td><td>210 9 Reissue claims in excess of 20 and over original patent</td></tr> <tr> <td colspan="3">SUBTOTAL (2) \$ 0 00</td> </tr> </tbody> </table>								Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid	101	710	201	355 Utility Filing Fee 710.00	106	320	206	160 Design Filing Fee	107	490	207	245 Plant Filing Fee	108	710	208	355 Reissue filing Fee	114	150	214	75 Provisional Filing Fee	SUBTOTAL (1) \$ 710.00				Total Claims	Extra *20	Fee From Below	Fee Paid	16	0	x 0.00	= 0.00	2	* 3	0	= 0.00	Multiple Dependant Claims				Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	102	18	201 9 Claims in excess of 20	102	80	202 39 Independent claims in excess of 3	104	206	204 130 Multiple dependent claim	109	78	209 39 Reissue independent claims over original patent	110	18	210 9 Reissue claims in excess of 20 and over original patent	SUBTOTAL (2) \$ 0 00																																																									
Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid																																																																																																																												
101	710	201	355 Utility Filing Fee 710.00																																																																																																																												
106	320	206	160 Design Filing Fee																																																																																																																												
107	490	207	245 Plant Filing Fee																																																																																																																												
108	710	208	355 Reissue filing Fee																																																																																																																												
114	150	214	75 Provisional Filing Fee																																																																																																																												
SUBTOTAL (1) \$ 710.00																																																																																																																															
Total Claims	Extra *20	Fee From Below	Fee Paid																																																																																																																												
16	0	x 0.00	= 0.00																																																																																																																												
2	* 3	0	= 0.00																																																																																																																												
Multiple Dependant Claims																																																																																																																															
Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description																																																																																																																													
102	18	201 9 Claims in excess of 20																																																																																																																													
102	80	202 39 Independent claims in excess of 3																																																																																																																													
104	206	204 130 Multiple dependent claim																																																																																																																													
109	78	209 39 Reissue independent claims over original patent																																																																																																																													
110	18	210 9 Reissue claims in excess of 20 and over original patent																																																																																																																													
SUBTOTAL (2) \$ 0 00																																																																																																																															

<b>SUBMITTED BY</b>			<i>Complete (if applicable)</i>	
Typed or Printed Name	Michael Tersillo			Reg. Number 42,180
Signature	Michael Tersillo	Date 10/18/00	Deposit Account User ID	

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Office, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS SEND TO Assistant Commissioner for Patents, Washington, DC 20231

PATENT  
Atty Dkt No: 24-AT-5990

CERTIFICATE OF MAILING BY EXPRESS MAIL TO  
THE COMMISSIONER OF PATENTS AND TRADEMARKS

Express Mail mailing label number: EL319732601US

Date of Mailing: October 19, 2000

I certify that the attached complete utility patent application of **Roy C. Challberg** for **CORE SUPPORT FOR AN F-LATTICE CORE OF A BOILING WATER NUCLEAR REACTOR**, including:

- Patent Application Transmittal (1 page)
- Fee Transmittal (in duplicate) (1 page)
- Nine (9) pages of specification; four (4) pages of claims; one (1) page of abstract
- Eleven (11) sheets of drawings
- Declaration and Power of Attorney of Roy C. Challberg (2 pages)
- Assignment of Roy C. Challberg (1 page)
- Assignment Recordation Cover Sheet (in duplicate) (1 page)
- Return post card

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. §1.10 on the date indicated above in an envelope addressed to Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.



\_\_\_\_\_  
Michael Tersillo  
Reg. No. 42,180  
Armstrong Teasdale LLP  
One Metropolitan Square, Suite 2600  
St. Louis, MO 63102  
314/621-5070

## CORE SUPPORT FOR AN F-LATTICE CORE OF A BOILING WATER NUCLEAR REACTOR

### BACKGROUND OF THE INVENTION

This invention relates generally to nuclear reactors and, more particularly, core support for F-lattice cores in nuclear reactors.

A known reactor pressure vessel (RPV) of a boiling water reactor (BWR) has a generally cylindrical shape and is closed at both ends, e.g., by a bottom head and a removable top head. A top guide is spaced above a core plate within the RPV. A core shroud, or shroud, surrounds the core plate and is supported by a shroud support structure. Particularly, the shroud has a generally cylindrical shape and surrounds both the core plate and the top guide. The top guide includes several openings, and fuel bundles are inserted through the openings and are supported by the core plate. The core plate includes a flat plate supported by a plurality of beams.

A plurality of openings are formed in the bottom head dome so that components, such as control rod drive assemblies, can extend within the RPV. As an example, for a control rod drive assembly, a control rod drive housing, for example, a tube, is inserted through the bottom head dome opening and a control rod drive is inserted through the control rod drive housing. The control rod drive is coupled to a control rod to position the control rod within the core.

A nuclear reactor core includes individual fuel assemblies that have different characteristics that affect the strategy for operation of the core. For example, a nuclear reactor core has many, e.g., several hundred, individual fuel bundles that have different characteristics. Such bundles preferably are arranged within the reactor core so that the interaction between the fuel bundles satisfies all regulatory and reactor design constraints, including governmental and customer specified constraints. In addition to satisfying the design constraints, since the core loading arrangement determines the cycle energy, i.e., the amount of energy that the reactor core generates

before the core needs to be refreshed with new fuel elements, the core loading arrangement preferably optimizes the core cycle energy.

In order to furnish the required energy output, the reactor core is periodically refueled with fresh fuel bundles. To optimize core cycle energy, the higher reactivity bundles may be positioned at an inner core location. To satisfy some design constraints, however, higher reactivity bundles generally are positioned at an outer core location. The most depleted fuel bundles, i.e., the bundles with the least remaining energy content, are removed from the reactor. The interval between refuelings is referred to as a cycle of operation.

During the course of the cycle of operation, the excess reactivity, which defines the energy capability of the core, is controlled in two ways. Specifically, a burnable poison, e.g., gadolinia, is incorporated in the fresh fuel. The quantity of initial burnable poison is determined by design constraints typically set by the utility and by the NRC. The burnable poison controls most, but not all, of the excess reactivity.

Control rods also control the excess reactivity. Specifically, the reactor core contains control rods which assure safe shutdown and provide the primary mechanism for controlling the maximum power peaking factor. The total number of control rods available varies with core size and geometry, and is typically between 50 and 269. The position of the control rods, i.e., fully inserted, fully withdrawn, or somewhere between, is based on the need to control the excess reactivity and to meet other operational constraints, such as the maximum core power peaking factor.

One known control rod includes a central portion having four radially extending blades. The blades define four fuel bundle channels, and when inserting the control rod into the core, the control rod is positioned so that one fuel bundle is positioned within each channel. Therefore, for example, approximately 100 control rods are included in a reactor having 400 fuel bundles.

To reduce the number of control rods necessary for efficient operation, the core of a nuclear reactor includes a plurality of fuel bundles and a plurality of large control rods. Each large control rod is about two times the width of a conventional control rod and includes four control rod blades extending radially from a central portion and arranged at right angles to each other. The blades define four fuel bundle receiving channels. The core is configured so that the control rods are arranged in a plurality of staggered rows with four fuel bundles in each receiving channel. This configuration is defined as an F-lattice configuration.

In this F-lattice configuration a fuel cell is formed by one large control rod and sixteen fuel bundles. The four blades of the control rod divide the fuel cell into four equal quadrants. The fuel bundles are arranged around the control rod so that there are four fuel bundles in each quadrant of the fuel cell. The core is formed from a plurality of fuel cells. In the F-lattice configuration with the large control rods arranged in staggered rows, each edge of a fuel cell is adjacent to and substantially parallel to a blade of a control rod.

The large control rod in an F-lattice configuration complicates the flat plate and beam support concept of the core plate because of the size of the control rod and the staggered arrangement of the rods. The staggered rod pattern permits very little clearance for the support beams.

Normal coolant flow entering the standard sized BWR fuel assemblies is single phased and slightly subcooled. The flow approaches the fuel support vertically upward and then turns horizontally as the flow enters the inlet to the fuel support. The flow then passes through an orifice that provides the required pressure drop, assuring the correct coolant distribution to low and high-powered fuel bundles. The flow then turns vertical again and enters the lower tie plate of the fuel assembly, being distributed around the individual fuel pins.

For the F-lattice configuration, the flow approaches the entrance to the fuel vertically but must flow directly past core plate support beams for about half of the entrances. The support beams obstruct the coolant flow and create flow separation

and bi-stable flow. These abnormal flow characteristics can influence the flow pattern at both the entrance and within the fuel assembly.

It would be desirable to provide a core support arrangement for F-lattice configured cores that provides identical flow entrance conditions for all the fuel assemblies.

#### BRIEF SUMMARY OF THE INVENTION

In an exemplary embodiment, a core plate assembly for a nuclear reactor includes a plurality of support beams, a flat plate positioned on top of the support beams, a plurality of control rod guide tube openings arranged in staggered rows, and a plurality of fuel supports extending through the flat plate.

The guide tube openings have a cruciform shape and include four slots extending radially from a central portion at right angles to each other. The slots define four fuel bundle receiving areas. Each guide tube opening is sized to receive a control rod guide tube.

Each fuel support includes a coolant flow inlet, a coolant flow outlet sized to receive a lower tie plate of a fuel bundle, and a coolant flow bore extending between the coolant flow inlet and the coolant flow outlet. The coolant flow inlet is offset from coolant flow outlet so that a centerline of the coolant flow inlet is parallel to a centerline of the coolant flow outlet. Each coolant flow inlet includes an orifice plate. The coolant flow inlets are positioned adjacent to a support beam, and the coolant flow outlets are positioned in a fuel bundle receiving area. Each fuel bundle receiving area includes four fuel supports to support four fuel bundles.

The above described core plate assembly provides unobstructed coolant flow inlets and therefore identical flow entrance conditions for all the fuel assemblies.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a sectional view, with parts cut away, of a boiling water nuclear reactor pressure vessel.

Figure 2 is a top schematic view of an F-lattice core configuration for the reactor pressure vessel shown in Figure 1.

5       Figure 3 is a top schematic view of a core plate for the F-lattice core configuration shown in Figure 2.

Figure 4 is a sectional schematic view of the core plate shown in Figure  
3.

Figure 5 is a sectional side view of a fuel bundle support.

10      Figure 6 is a sectional side view of a fuel bundle support in accordance with an embodiment of the present invention.

Figure 7 is a top schematic view of a core plate including the fuel bundle support shown in Figure 6.

15      Figure 8 is a top schematic view of a core plate including fuel bundle supports in accordance with another embodiment of the present invention.

Figure 9 is an enlarged top view of the fuel bundle support shown in Figure 8.

Figure 10 is a cross sectional view through line A-A.

20      Figure 11 is a top schematic view of a core plate including fuel bundle supports in accordance with another embodiment of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

Figure 1 is a sectional view, with parts cut away, of a boiling water nuclear reactor pressure vessel (RPV) 10. RPV 10 has a generally cylindrical shape

and is closed at one end by a bottom head 12 and at its other end by a removable top head 14. A side wall 16 extends from bottom head 12 to top head 14. A cylindrically shaped core shroud 20 surrounds a reactor core 22. Shroud 20 is supported at one end by a shroud support 24 and includes a removable shroud head 26 at the other end. An annulus 28 is formed between shroud 20 and side wall 16.

Heat is generated within core 22, which includes fuel bundles 36 of fissionable material. Water circulated up through core 22 is at least partially converted to steam. Steam separators 38 separates steam from water, which is recirculated. Residual water is removed from the steam by steam dryers 40. The steam exits RPV 10 through a steam outlet 42 near vessel top head 14.

The amount of heat generated in core 22 is regulated by inserting and withdrawing control rods 44 of neutron absorbing material, such as for example, hafnium. To the extent that control rod 44 is inserted into fuel bundle 36, it absorbs neutrons that would otherwise be available to promote the chain reaction which generates heat in core 22. Control rod guide tubes 46 maintain the vertical motion of control rods 44 during insertion and withdrawal. Control rod drives 48 effect the insertion and withdrawal of control rods 44. Control rod drives 48 extend through bottom head 12.

Fuel bundles 36 are aligned by a core plate assembly 50 located at the base of core 22. A top guide 52 aligns fuel bundles 36 as they are lowered into core 22. Core plate 50 and top guide 52 are supported by core shroud 20. Fuel bundles 36 have a substantially square cross section. In alternative embodiments, fuel bundles can have a rectangular or other polygon cross section.

Figure 2 is a top schematic view of an F-lattice configuration of core 22 of reactor pressure vessel 10. Substantially standard size fuel bundles 36 and large control rods 44 are utilized in core 22. Each large control rod 44 is sized to provide poison control for sixteen conventional size fuel bundles 36. Conventional size fuel assemblies 36 and large control rods 44 are arranged in an F-lattice configuration 54 to facilitate minimizing the number of control rod drives and control rods. F-lattice

configuration 54 has large control rods 44 in staggered rows 56 with sixteen conventional fuel bundles 36 surrounding each large control rod 44.

Figure 3 is a top schematic view of core plate assembly 50 for F-lattice core configuration 54, and Figure 4 is a top sectional schematic view of core plate assembly 50. Referring to Figures 3 and 4, core plate assembly 50 includes a flat plate 58 supported by a plurality of support beams 60. Flat plate 58 includes a plurality of control rod guide tube openings 62 sized to receive cruciform shaped control rod guide tubes 46. Each guide tube opening 62 has a cruciform shape and includes slots 64, 66, 68, and 70 extending radially from a central portion 72 at right angles to each other. Slots 64, 66, 68, and 70 define four fuel bundle receiving areas 74. Core plate assembly 50 also includes four fuel bundle supports 76 located in each fuel bundle receiving area 74. Each fuel bundle support 76 extends through flat plate 58 and includes a coolant flow outlet 78.

Figure 5 is a sectional side view of a known fuel bundle support 80 extending through a core plate 82. Fuel support 80 includes a coolant flow inlet 84 and a coolant flow outlet 86. A bore 88 extends from inlet 84 to outlet 86. An orifice plate 90 is located inside bore 88. Coolant flows into flow inlet 84, through bore 88 and flow outlet 86 and into fuel bundle 36. Coolant flow inlet 84 and coolant flow outlet 86 are coaxial and centerline 92 passes through the center of both inlet 84 and outlet 86. Coolant flow outlet 86 is configured to receive a lower tie plate 94 of a fuel bundle 36.

Because of the geometry of F-lattice core configuration 54, a core plate support beam 96 obstructs coolant flow inlet 84 of about 50% of fuel bundle supports 80 located on core plate 82. The obstruction of flow inlet 84 caused by support beam 96 can create flow separation and bi-stable flow which can influence the coolant flow pattern at both coolant flow inlet 84 and within fuel bundle 36.

Figure 6 is a sectional side view of a fuel bundle support 98, in accordance with an embodiment of the present invention, extending through flat plate 58 of core plate assembly 50. Fuel support 98 includes a coolant flow inlet 100, a

coolant flow outlet 102 sized to receive lower tie plate 94 of a fuel bundle 36. A coolant flow bore 104 extends between coolant flow inlet 100 and coolant flow outlet 102. Coolant flow inlet 100 is offset from coolant flow outlet 102 so that a centerline 106 of coolant flow inlet 100 is parallel to a centerline 108 of coolant flow outlet 102.

5 Coolant flow inlet 100 includes an orifice plate 110. Coolant flow inlet 100 is positioned adjacent to a support beam 60 of core plate assembly 50.

Figure 7 is a top schematic view of core plate assembly 50. Core plate assembly 50 includes a plurality of fuel bundle supports 98 and a plurality of cruciform shaped control rod guide tube openings 62 arranged in an F-lattice core configuration 54. Four fuel bundle supports 98 are located in each fuel bundle receiving area 74. Because of the offset configuration of coolant flow inlet 100 and coolant flow outlet 102 in fuel bundle supports 98, each coolant flow inlet 100 is positioned adjacent a core plate support beam 60, and therefore, there are no obstructions of coolant flow inlets 100.

15 Figure 8 is a top schematic view of a core plate assembly 112 that includes a plurality fuel bundle supports 114 in accordance with another embodiment of the present invention. Figure 9 is an enlarged top view of fuel bundle support 114, and Figure 10 is a cross sectional view of fuel bundle support 114 through line A-A. Core plate assembly 112, similar to core plate assembly 50 described above, includes a flat plate 116 supported by a plurality of support beams 118, a plurality of control rod guide tube openings 120, and a plurality of fuel bundle receiving areas 122.

20

Each fuel bundle support 114 supports four fuel bundles 36 (see Figure 6) and includes four coolant flow inlets 124 and four coolant flow outlets 126. Each fuel bundle receiving area 122 contains one fuel bundle support 114.

25 Each coolant flow inlet 124 has a corresponding coolant flow outlet 126 and a bore 128 extending from coolant flow inlet 124 to corresponding coolant flow outlet 126. Coolant flow inlet 124 is offset from corresponding coolant flow outlet 126 so that a centerline 130 of coolant flow inlet 124 is parallel to a centerline 132 of corresponding coolant flow outlet 128. An orifice plate 134 is located in each

coolant flow inlet 124. Additionally, coolant flow inlets 124 are located in fuel bundle support 114 so that each coolant flow inlet 124 is the same distance from a support beam 118. Particularly, a distance "B" from coolant flow inlet 124 is the same for all coolant flow inlets 124 in fuel bundle support 114.

5           The above described core plate assembly 50 with fuel bundle supports 98 and core plate assembly 112 with fuel supports 114 provide unobstructed coolant flow inlets and therefore identical flow entrance conditions for all fuel assemblies 36.

10          Figure 11 is a top schematic view of a core plate assembly 136 that includes a plurality fuel bundle supports 138 in accordance with another embodiment 15 of the present invention. Core plate assembly 136, similar to core plate assembly 112 described above, includes a flat plate 140 supported by a plurality of support beams 142, a plurality of control rod guide tube openings 144, and a plurality of fuel bundle receiving areas 146. Each fuel bundle receiving area 146 includes one fuel bundle support 138, and each fuel bundle support is configured to support one large fuel bundle (not shown). Each large fuel bundle is approximately 1.5 times the size of a standard fuel bundle 36.

20          Fuel support 138 includes a coolant flow inlet 148 and a coolant flow outlet 150. A coolant flow bore (not shown) extends between coolant flow inlet 148 and coolant flow outlet 150. Coolant flow inlet 148 is offset from coolant flow outlet 150. Coolant flow inlet 148 is positioned adjacent to a support beam 142 of core plate assembly 136.

While the invention has been described in terms of various specific embodiments, those skilled in the art will recognize that the invention can be practiced with modification within the spirit and scope of the claims.

WHAT IS CLAIMED IS:

1. A core plate assembly for a nuclear reactor, the reactor comprising a plurality of large control rods, a plurality of cruciform shaped control rod guide tubes, and a plurality of fuel bundles having lower tie plates, said core plate assembly comprising:

5 a flat plate;

a plurality of support beams, said flat plate positioned on top of said support beams;

10 a plurality of control rod guide tube openings, each said guide tube opening sized to receive a control rod guide tube, said control rod guide tube openings arranged in staggered rows;

15 a plurality of fuel supports extending through said flat plate, each said fuel support comprising:

a coolant flow inlet;

20 a coolant flow outlet sized to receive a lower tie plate of a fuel

bundle; and

a coolant flow bore extending between said coolant flow inlet and said coolant flow outlet, said coolant flow inlet offset from said coolant flow outlet so that a centerline of said coolant flow inlet is parallel to a centerline of said coolant flow outlet.

25 2. A core plate assembly in accordance with Claim 1 wherein said guide tube openings have a cruciform shape and comprise four slots extending radially from a central portion at right angles to each other, said slots defining four fuel bundle receiving areas.

3. A core plate assembly in accordance with Claim 1 wherein each said coolant flow inlet comprises an orifice plate.

4. A core plate assembly in accordance with Claim 2 wherein said coolant flow inlets are positioned adjacent a support beam, and said coolant flow outlets are positioned in a fuel bundle receiving area.

5. A core plate assembly in accordance with Claim 2 wherein each said fuel bundle receiving area comprises four fuel supports.

6. A core plate assembly in accordance with Claim 2 wherein each said fuel bundle receiving area comprises one fuel support.

7. A core plate assembly in accordance with Claim 2 wherein each fuel support further comprises:

10 four coolant flow inlets;

four coolant flow outlets sized to receive a lower tie plate of a fuel bundle; and

15 four coolant flow bores, each flow bore extending between a corresponding coolant flow inlet and a corresponding coolant flow outlet, said coolant flow inlets offset from said corresponding coolant flow outlets so that a centerline of said coolant flow inlet is parallel to a centerline of said corresponding coolant flow outlet, said coolant flow inlets positioned adjacent a support beam, and said coolant flow outlets positioned in a fuel bundle receiving area.

20 8. A core plate assembly in accordance with Claim 7 wherein each said fuel bundle receiving area comprises one fuel support.

9. A core for a nuclear reactor comprising:

a plurality of fuel bundles, each fuel bundle comprising a lower tie plate;

a plurality of cruciform shaped large control rods;

25 a plurality of cruciform shaped control rod guide tubes; and

a core plate assembly comprising:

a flat plate;

5                   a plurality of support beams, said flat plate positioned on top of  
said support beams;

10                  a plurality of control rod guide tube openings, each said guide  
tube opening sized to receive a control rod guide tube, said control rod guide  
tube openings arranged in staggered rows; and

15                  a plurality of fuel supports extending through said flat plate,  
each said fuel support comprising:

20                  a coolant flow inlet;

25                  a coolant flow outlet sized to receive a lower tie plate of  
a fuel bundle; and

30                  a coolant flow bore extending between said coolant flow  
inlet and said coolant flow outlet, said coolant flow inlet offset from  
said coolant flow outlet so that a centerline of said coolant flow inlet is  
parallel to a centerline of said coolant flow outlet.

35                  10. A core in accordance with Claim 9 wherein said guide tube  
openings have a cruciform shape and comprise four slots extending radially from a  
central portion at right angles to each other, said slots defining four fuel bundle  
receiving areas.

40                  11. A core in accordance with Claim 9 wherein each said coolant  
flow inlet comprises an orifice plate.

45                  12. A core in accordance with Claim 10 wherein said coolant flow  
inlets are positioned adjacent a support beam, and said coolant flow outlets are  
25                  positioned in a fuel bundle receiving area.

13. A core in accordance with Claim 10 wherein each said fuel bundle receiving area comprises four fuel supports.

14. A core in accordance with Claim 10 wherein each said fuel bundle receiving area comprises one fuel support.

5 15. A core in accordance with Claim 10 wherein each fuel support further comprises:

four coolant flow inlets;

four coolant flow outlets sized to receive a lower tie plate of a fuel bundle; and

10 four coolant flow bores, each flow bore extending between a corresponding coolant flow inlet and a corresponding coolant flow outlet, said coolant flow inlets offset from said corresponding coolant flow outlets so that a centerline of said coolant flow inlet is parallel to a centerline of said corresponding coolant flow outlet, said coolant flow inlets positioned adjacent a support beam, and said coolant flow outlets positioned in a fuel bundle receiving area.

15

16. A core in accordance with Claim 15 wherein each said fuel bundle receiving area comprises one fuel support.

CORE SUPPORT FOR AN F-LATTICE CORE OF A  
BOILING WATER NUCLEAR REACTOR

ABSTRACT OF THE DISCLOSURE

A core plate assembly for a nuclear reactor includes a plurality of support beams, a flat plate positioned on top of the support beams, a plurality of control rod guide tube openings arranged in staggered rows, and a plurality of fuel supports extending through the flat plate. Each guide tube opening has a cruciform shape defines four fuel bundle receiving areas. Each fuel support includes a coolant flow inlet, and a coolant flow outlet sized to receive a lower tie plate of a fuel bundle. The coolant flow inlet is offset from coolant flow outlet so that a centerline of the coolant flow inlet is parallel to a centerline of the coolant flow outlet. The coolant flow inlets are positioned adjacent a support beam, and the coolant flow outlets are positioned in a fuel bundle receiving area.




FIG. 1

2/11




FIGURE 2

3/11




FIGURE 3

4/11




FIGURE 4




FIGURE 5





FIGURE 6



## FIGURE 7

8/11




FIGURE 8

9/11




Figure 9

10/11




FIGURE 10




FIGURE 11

**DECLARATION AND POWER OF ATTORNEY**

Attorney's Docket No.  
24-AT-5990

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **CORE SUPPORT FOR AN F-LATTICE CORE OF A BOILING WATER NUCLEAR REACTOR**,  
the specification of which:

(check one)  is attached hereto

was filed on \_\_\_\_\_ as Application Serial No. \_\_\_\_\_,  
and was amended on \_\_\_\_\_.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations §1.56(a).

I hereby claim priority benefits under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112. I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

<u>Application Serial No.</u>	<u>Filing Date</u>	<u>Status (patented, pending, abandoned)</u>

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below:

<u>Application Serial No.</u>	<u>Filing Date</u>	Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (*list name and registration number*)

John S. Beulick, Reg. No. 33,338, and Michael Tersillo, Reg. No. 42,180, of Armstrong Teasdale LLP, One Metropolitan Square, Suite 2600, St. Louis, MO 63102-2740); James E. McGinness, Reg. No. 33,260, GE Nuclear Energy, PO Box 780, 3901 Castle Hayne Road, M/CA11, Wilmington, NC 28401; and James Mitchell, Reg. No. 25,602, 3135 Easton Turnpike, Fairfield, CT 06431

Send Correspondence to:

John S. Beulick  
Armstrong Teasdale LLP  
One Metropolitan Square, Suite 2600  
St. Louis, MO 63102-2740

Direct Telephone Calls To:

John S. Beulick  
314/621-5070

DECLARATION AND POWER OF ATTORNEY	Attorney's Docket No. 24-AT-5990
-----------------------------------	-------------------------------------

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application and any patent issued thereon.

**SOLE OR FIRST INVENTOR:**

Full Name: Roy C. Challberg

Signature: Roy C. Challberg

Date: 10.12.2066

Residence: Livermore, CA 94550

Citizenship: U.S.A.

Post Office Address: 178 Cameo Drive, Livermore, CA 94550